

Start-up of aerobic granular sludge

Results of the first AGS start-up in the Nordic countries

Jennifer Ekholm, Mark de Blois,
Frank Persson, Britt-Marie Wilén,
David Gustavsson, Jerry Johansson,
Bart de Bruin



STRÖMSTADS
KOMMUN



TANUMS
KOMMUN

H2OLAND



CHALMERS
UNIVERSITY OF TECHNOLOGY



sweden
water
research



EnviDan



Royal
HaskoningDHV
Enhancing Society Together



TU Delft



UPPSALA VATTEN



KÄPPALA



Gryaab



VASYD



VÄSTERVIK
MiljöEnergi




Svenskt Vatten

Aerobic granular sludge (AGS)


Granular sludge formed due to

- High feeding concentration
- Wash out of slow settling sludge
- Anaerobic feed favours slow growers



AGS opens the door for

- Compact **and** energy efficient treatment
- Simultaneous C, N, P removal




Bengtsson *et al.* (2018)

Nereda® technology

Optimised SBR cycle:


- Simultaneous influent feed and effluent discharge
- Simultaneous biological removal of organic, nitrogen and phosphorus components
- Fast settling phase



Picture: Bengtsson et. al. 2017

Österröd WWTP in Strömstad, Sweden

- Reconstruction to increase capacity
- AGS and conventional activated sludge (CAS) in parallel
- Pre-settling added
- Design: 30,000 PE (max in summer)
- Biological treatment capacity 600 m³/h (60% to AGS)



Start-up of AGS

Start-up under real conditions have challenges

- Availability of granulated sludge/selection of activated sludge for seeding
- Operation to ensure both granulation and sufficient treatment

Over 30 full-scale AGS have been started up, but not many are scientifically documented

General challenges specific at Österröd WWTP

- Low temperatures during winters
- Large load variations
- Long lasting high flows
- Incoming load > the design (CAS under reconstruction during start-up)

Objective

Evaluate the start-up of the first AGS in the Nordic countries in terms of

- Inoculum
- Granulation
- Process performance
- Microbial community development
- Influence of local conditions

Methods

- Chemical analyses
- MLSS, SVI and granule size distribution
- Cycle studies
- Activity batch tests
- DNA and FISH analysis



Picture: measurement of granule size distribution


Start-up at Österröd WWTP

Start-up date: 26 June 2018

Study period: – August 2019


Reactor 1

- Swedish activated sludge, SBR with bio-P
- Start conc 3.4 g/L



Reactor 2

- Aerobic granular sludge from the Netherlands
- Start conc 3.6 g/L



Strategy


- Gradual flow load increase

Wastewater characteristics


| Flow proportional averages | Flow | BOD ₇ | COD | COD filtered | P _{tot} | N _{TKN} | NH ₄ ⁺ -N |
|----------------------------|-------------------|------------------|------|--------------|------------------|------------------|---------------------------------|
| | m ³ /d | mg/L | mg/L | mg/L | mg/L | mg/L | mg/L |
| July - August | 2000 | 140 | 350 | 190 | 5.6 | 56 | 51 |
| September - June | 3800 | 66 | 160 | 74 | 3.3 | 33 | 26 |

| | BOD ₇ / N _{TKN} |
|-----------|-------------------------------------|
| Jul - Aug | |
| Average ± | 2.6 |
| SD | ± 0.7 |
| Sep - Jun | |
| Average ± | 2.0 |
| SD | ± 0.6 |


Many samples are grab samples




Results – sludge characteristics




Re-seeding reactor 1 from reactor 2



Reactor 1




Reactor 2




Results - granule size distribution

Reactor 1: more large granules after re-seeding


Reactor 2: increase of large granules the whole year




Specific loading COD



Design- and actual load to AGS




- The actual nitrogen loads were higher than design loads




- The actual organic loads were lower than design loads


Results – process performance



Results – process performance





Results – process performance



Next

- Hydrolysing primary sludge and bypass of non-settled water to increase N and P removal
- More data processing
- More activity batch tests
- DNA and FISH analysis
- Temperature study in lab-scale



Pictures: Jennifer Ekholm

1 mm

Conclusions

- The start-up was challenging due to **higher N-loads than design** (reconstruction of CAS) combined with low temperatures.
- **Low BOD₇/N** in AGS influent makes denitrification down to low contents difficult.
- Enhanced bio-P suffers from low VFA- and dissolved COD-contents.
- Nitrification works – but limited nitrification rates combined with high flows (short cycle times) can give challenges during winter.
- Granules with much filamentous outgrowth still had very good SVI and stay in the reactors.
- Good granulation has been achieved in both reactors and in reactor 1 re-seeding was necessary to be able to achieve better treatment results quicker.
- Many technical problems had to be dealt with, such as sludge handling and online instrumentation → next year is expected to be better.

Thank you for your attention!

Jennifer Ekholm

E-mail: jennifer.ekholm@chalmers.se

Special thanks to

Strömstad municipality: Karin Myring, Jerry Johansson, Tim van Erp, Robert Larsson, Karl Beckman and Patrik Johansson

H2OLAND: Mark de Blois, Jonatan Flodin and Sebastian Engström

Sweden Water Research: David Gustavsson

Chalmers: Britt-Marie Wilén and Frank Persson

RoyalHaskoningDHV: Bart de Bruin, Sjoerd Kerstens and Andreas Giesen



Picture: Britt-Marie Wilén